

▶ ECOMIX® application and efficiency

Tank size	Ecomix bags 25 liters (0.9 ft ³)	EUROPE		USA	
		Capacity: kg CaCO ₃ / kg NaCl	Flow rate, m ³ /h	Capacity: grains / lbs NaCl	Flow rate, gpm
Ecomix 1035	1	0,88 @ 2,5	1,3	13 500 @ 5,5	5,7
Ecomix 1054	1,5	1,30 @ 3,7	1,3	20 200 @ 8,3	5,7
Ecomix 1252	2	1,75 @ 5,0	1,8	27 000 @ 11,0	7,9
Ecomix 1354	2,5	2,20 @ 6,2	2,2	33 700 @ 13,8	9,7
Ecomix 1465	3	2,65 @ 7,5	2,5	40 500 @ 16,5	11,0
Ecomix 1665	4	3,50 @ 10,0	3,3	53 900 @ 22,0	14,5

▶ ECOMIX® application and efficiency

	MAX Concentration limits		Removal efficiency, max %	
			Type A	Type C
Hardness*	ppm CaCO ₃ 750	gpg 45	97	
Iron	ppm 15		98	
Manganese	ppm 3		98	
COD (including tannins)	ppm KMnO ₄ 80		50	80
Ammonia	ppm 4		90	

*limit installed due to sodium effluent

About ECOSOFT, manufacturer of ECOMIX®

Ecosoft is a professional water purification company with production and sales offices in Germany and Ukraine. Since 1991 the company produces and distributes filtration materials, POU filters, residential, commercial and industrial water treatment systems. Ecosoft products are widely used by water professionals worldwide.



Ecosoft Water Systems GmbH
Tel: +49 (0) 2157 87 56 497
Schwanenhaus 24
41334 Nettetal,
Germany

www.ecosoft.ws

© Ecosoft SPC - 2014

ECOMIX®

MULTI-PURPOSE
SOFTENING
MATERIAL
for problem water



SIMPLE SOLUTION
FOR 5 PROBLEMS

- hardness
- iron
- manganese
- tannins
- ammonia

Used by water treatment specialists
throughout the world. Since 1998.



Ecomix is certified for drinking water application in European Union by TÜV SÜD

What is ECOMIX®?

ECOMIX® is an advanced multi-purpose softening material for problem water.

Ecomix® is a turnkey solution for removing hardness, iron, manganese, tannins and ammonia in one filter. Ecomix comprises 5 special components made from natural and synthetic materials. After loading a softener with Ecomix, it separates into five layers ensuring efficient and robust operation.

Using ECOMIX® is more effective than traditional filtration techniques for your iron problems, because ECOMIX®:

- ▶ Removes ferrous, ferric, organic and colloidal iron and manganese at the highest concentration levels on the market;
- ▶ Removes color of water caused by presence of tannins;
- ▶ Works at low TDS, low hardness, high H₂S and pH 5-9;
- ▶ Works with low salt consumption.

Ecomix® approach has created new perspectives for numerous water treatment companies:

- ▶ Simple and manageable technology for treatment of high iron problem water that only takes a simple water quality test to provide a solution.
- ▶ Works in normal softeners - no extra inventory is needed for water with iron.
- ▶ Easy assembling, installation and maintenance.
- ▶ Low distribution and deployment costs.

Learn more and download at www.ecosoft.ws

MULTI-PURPOSE
SOFTENING
MATERIAL
for problem water



made
in
Germany